

E DIN VDE 0611 Teil 6 適合ヒューズホルダー端子台仕様



EKFD4-2・EKFD4-2-(*) CU/ch/cg

ライセンス No.

(*) には、極数が入ります。


R 9750811

ヒューズホルダー端子台をお買いあげいただきありがとうございます。

DIN VDE規格適合端子台はこの説明書をよくお読みのうえ正しくご使用下さい。

【1】取扱い上のご注意

- ①使用電線範囲 : 0.5~6mm
- ②適合ヒューズ : 5×20
- ③接続可能電線数 : 1本
- ④被覆むき長さ :
(mm)



⑤このヒューズホルダー端子台は短絡保護にのみ使用することができます。

【2】一般仕様

- ①定格絶縁電圧 : 250V
- ②定格インパルス耐電圧 : 4kV
- ③定格電流 : 6.3A (6mm 接続時)
- ④締付トルク : 0.7N・m
- ⑤保護構造 : IP10
- ⑥最大組立可能極数 : 230極
- ⑦電力消費 : Pvk=8.36W (単体), 4.78W (組端子台)

【3】標準使用状態

- ①周囲温度 : -5℃~40℃
- ②相対湿度 : 最高温度40℃のもとで50%以下
- ③標高 : 2000m以下
- ④汚損度 : 3
- ⑤運搬及び保管条件 : -25℃~55℃及び24時間を超えない短期間で70℃以下

【4】アクセサリ (端子台をレールに組付けるときは、次のアクセサリをご使用下さい。)

- ①終末板 : EKFD4-a
- ②レール : UK-c, EK-ch, EK-cg
- ③終端止め : EK-b
- ④記名板 : EK-5e, EK-6e



東朋テクノロジー株式会社

YOSHIDA 端子台事業部

Specification of the terminal blocks to E DIN VDE 0611 Teil 6



EKFD4-2 · EKFD4-2- (*) CU/ch/cg

Certificate No.

R 9750811


(*): To show the number of blocks

Thank you for your purchasing the YOSHIDA fuse-holder terminal blocks.

Please read this leaflet carefully, before using the fuse-holder terminal blocks.

[1] Caution for use

- ① Conductor range : 0.5- 6mm²
- ② Appropriate fuse-links : 5 x 20
- ③ Number of conductors : One (1)
- ④ Strip dimension (mm) :



- ⑤ This fuse-holder terminal block is designed for short-circuit protection only.

[2] General specification

- ① Rated insulation voltage : 250V
- ② Rated impulse withstand : 4kV
voltage
- ③ Current rating : 6.3A (at 6mm²)
- ④ Tightening torque range : 0.7N · m
- ⑤ Protection degree : IP10
- ⑥ Maximum number of blocks : 230 blocks
- ⑦ Power dissipation : P_{vk} = 8.36W (SINGLE) , 4.78W (COMPOUND)

[3] Normal service conditions

- ① Ambient air temperature : -5°C to 40°C
- ② Humidity : Not exceed 50% at a maximum temperature of 40 °C
- ③ Altitude : Not exceed 2000m
- ④ Pollution degree : 3
- ⑤ Condition during transport and storage : -25 °C to 55°C and for short periods not exceeding 24 hours, up to 70°C

[4] Accessories (when mounting the fuse-holder terminal blocks on a rail, use the following accessories.)

- ① End Plate : EKFD4-a
- ② Rail : UK-c, EK-ch, EK-cg
- ③ End Bracket : EK-b
- ④ Marking Card : EK-5e, EK-6e



Toho Technology Corp.

KYOTO Yoshida Terminal Block Division JAPAN